ARMED WITH EVERY ADVANTAGE, DURING A LONG HEAVY HAUL

The Mack Defense Line Haul is a commercially-based Mack Anthem[®] – designed to haul up to 60 Ton payloads. The Mack Defense Line Haul challenges your expectations of a conventional transport truck – while meeting all military requirements. Efficiency and durability are built into every component, reducing your maintenance costs while maximizing uptime. It is powered by the fuel-efficient, 13-liter Mack MP8 engine that provides plenty of horsepower (440 HP), with low-end torque up to 1,600 lb-ft to haul over any grade. Steep grades to long hauls, the Mack Defense Line Haul has the power to handle heavy equipment and the efficiency to run longer.



MACK DEFENSE LINE HAUL

EXTENDED CAB SPECIFICATIONS

- 48" Mack® flattop extended cab
- (1) 12 Volt DC power outlet
- Dual fire extinguishers
- Multiple storage locations under bunk
- Convenient extended cab control panel
- Full walk through to sleeping quarters
- (DAY CAB OPTION ALSO AVAILABLE)



LINE HAUL

WEIGHTS/DIMENSIONS

GVWR: 86,000 lbs GCWR: 160,000 lbs Wheel Configuration: 6x4 Frame: 300mm X 90mm X 9.5mm with steel reinforcement frame liner Wheelbase: 204" Platform: 90"

POWERTRAIN

Type: Mack 13 Liter, MP8 440 Max Power: 440 HP Max Torque: 1660 lb-ft Engine Brake: Engine brake plus exhaust pressure governor Air Dryer: WABCO 1200UP w/o turbo cut-off valve, w/coalescing oil filter Air System: Meritor®/Wabco 636 (37.4 cfm) w/o clutch Starter: 12 Volt DELCO® 39MT-MXT Alternator: 12V alternator, with power outputs of 130 to 270 Amp ratings

DRIVELINE/TRANSMISSION

 Driveline: SPICER SPL350XL "Extended Lube Series" or inter axle -SPICER SPL250HDXL "Extended Lube Series"
Transmission: Mack TMD12ADO-HD mDRIVE HD 12 SP, Export (Overdrive)
Brakes: Meritor[®] "S" CAM Type 16.5"x6" Q+ front, Proprietary Z-CAM 16.5"x8" rear
ABS System: Mack Road Stability Advantage Bendix ABS/ATC/ESP W/YAW Control
Front Tires: 315/80R22.5 X Works Z Michelin
Rear Tires: 315/80R22.5 X Works Z Michelin (All positions)

AXLES/SUSPENSION

Front Axle: Mack FXL16.0 straights spindle with unitized bearings Front Suspension: Mack Progressive Taperleaf 16,000 lb (7,300 kg) ground load rating Rear Axle Bogie: 70,000 lb Meritor[®] Carrier Ratio: 4.55 Rear Suspension: 70K Parabolic leaf

CAB/CHASSIS

Driver Seat (non-armored): Mack-air, high back, 1 chamber air lumbar Passenger Seat (non-armored): Mack-fixed, high back Mirrors (both sides): Aero mirror - body color, heated/motorized, wide angle, w/o lamps Spare Tire: Option Left Side Fuel Capacity: 50 to 142 gallon options, aluminum or steel Right Side Fuel Capacity: Optional

CUSTOMIZED OPTIONS AVAILABLE TO MEET MISSION REQUIREMENTS

FOR MORE INFORMATION VISIT MACKDEFENSE.COM

Weights, dimensions and features are given for reference and may be modified according to the choice of certain options. Mack Defense, LLC, reserves the right to modify the above specifications without prior notification.

©2021 Mack Trucks, Inc. All rights reserved. Mack, Mack and the Bulldog design, Bulldog and all other marks contained herein are registered trademarks of Mack Trucks, Inc. and/or Mack Trucks, Inc. Affiliated companies. All other marks contained herein are the property of their respective owners.

